



FILTER CLEAN

Degreases and
Improves Filter Efficiency

ITEM NO. 1-2701SPA

KEEP OUT OF REACH OF CHILDREN
WARNING
IRRITATING TO EYES AND SKIN

See first aid statement and other
precautions on back panel.

Net Contents 1 Quart (32 fl. oz.)

ITEM NO. 1-2701SPA



This liquid product greatly improves filter life and efficiency. It is specially made to cleanse suntan oil and grease as well as scale and mineral deposits from spa filters of all types: cartridge, sand, and D.E. Regular use of this product will assure proper filtration.

DIRECTIONS FOR USE

When preparing or using this product, take care not to splash, drip, or use, on surfaces such as ceramic, linoleum, formica brand counter surfaces, carpeting, etc. as etching or discoloration of these surfaces may take place. This product is intended only for use as a spa filter cleaner.

SAND FILTERS: Turn off inlets and outlets for all chemical feeders. Close main drain and place filter in backwash position. Slowly add one quart of this product through strainer while backwashing. This product can also be added through the sand fill port. Run filter until product begins to come out of the backwash water or until the product is seen through a filter viewing cell. Soak filter for 30 to 60 minutes. After soaking, backwash filter until water comes out clean and foam clears. Reverse procedure and start normal filter operation. For sand filters containing more than 300 pounds of sand, add two quarts of this product.

CARTRIDGE FILTERS: Stop filter operation. Bleed off excess pressure through the filter safety valve. Open filter unit, remove cartridge from filter, and rinse excess loose dirt with a water hose from top to bottom. Place cartridge into a bucket and add 1 quart of product and 5 gallons water. Make sure filter unit is completely covered by the cleaner. Soak 30 to 60 minutes. After soaking, rinse with hose at maximum pressure to remove excess filter cleaner or until foam residue is completely washed off. Re-install cartridge and resume normal filter operation.

DIATOMACEOUS EARTH FILTERS: Stop filter operation. Bleed off excess pressure through safety valve. Remove filter elements (grids) from filter and rinse off excess dirt with a hose from top to bottom. Place grids in a bucket and add one quart of this product and 5 gallons water. Make sure grids are fully immersed in cleaner. Soak 30 to 60 minutes. After soaking, rinse out excess filter cleaner with hose at maximum pressure. Re-install grid and add new filter media. Resume normal filter operation.

WARNING

This product contains disodium trioxosilicate. Irritant to eyes, skin and mucous membranes. Avoid contact with skin, eyes, or clothing. Harmful if swallowed. Do not inhale or swallow. Do not mix with chlorine-type bleaches or other household chemicals.

FIRST AID

EYE CONTACT: Flush thoroughly with plenty of water for at least 15 minutes. Get prompt medical attention.

IF SWALLOWED: DO NOT INDUCE VOMITING. If conscious, give 1 to 2 glasses of water and call physician immediately. Never give anything by mouth to an unconscious person.

SKIN CONTACT: Flush area with plenty of water, then with soap and water. If irritation persists, get medical attention. Remove and wash clothing before reuse.

REV012217

32 oz.

30 oz.

28 oz.

26 oz.

24 oz.

22 oz.

20 oz.

18 oz.

16 oz.

14 oz.

12 oz.

10 oz.

8 oz.

6 oz.

4 oz.

2 oz.